


Specification

Solarix

Pole Street Light



30W

Order code DLOH03020006

Light head Watz

LED Power 30W

Luminous flux (lm) >4,200 lm

Power of solar module 200W

Vertical solar module Q100 2pc


Battery capacity 12.8V 307WH

System voltage 12V-MPPT

Pole Height 5 meters

Warranty 3 Years

Module Specification



Model: DLQ100

Peak power /Pm(W): 100W

Vmp: 18V

Imp: 5.56A

N.G / G.W 14.70 / 16.80 Kg

Cable & connector 2.5mm2 with MC4

Solar cell efficiency 20.50%

Solar cell type: MONO cell

Modular Dimension: L=1160W=228mm

Structure material Aluminium alloy

Working temp. -30°C`70°C

Warranty 5 Years

Life time >20 years

Patented Yes



Solarix

Specification

Street Light



WATZ series as the pioneer model of high power all in two solar led street light, it is a integrated solar street Light combined ultra brightness, intelligent programable MPPT controller and lifePO4 battery pack, all these components are integrated inside of light fixture, Solar light head are connected to solar panel by universal MC4 plugs.

Big capacity LifePO4 battery pack is adopt, and it could work continuously with high power, because solar panel is separated from light head, then customer can choose a suitable power of solar panel according their local solar radiation to ensure enough power can be generated daily to meet the power consumption of light.

Model: DLOAI-U30W

Rated power

LED SMD3030

Charging time

Discharging time

Battery autonomy

Working temp.

LifePO4 Battery

Solar Panel

Luminous Flux (lm)

30W

72 nos

>4200 lm

5 hours

>20 hours

2~3 days

-15°C~ + 70°C

12.8V 307WH

80W 18V

IP rating IP65

CCT 3000K/4000K/5700K

Dimensions:

